



Specifications

Material

Insulator: Polymer LCP, UL94V-0
Contact: Copper Alloy

Plating

See Ordering Grid

Electrical

Current Rating: 1 Amp *per pin*
Contact Resistance: 20 mΩ max.
Insulating Resistance: 1000 MΩ min.
Dielectric Withstand Voltage: 300V AC

Mechanical & Environmental

Operating Temperature: -40°C to +105°C
Soldering Process:
IR Reflow: 260°C for 10 sec.
Wave: 250°C for 5-10 sec
Manual Solder: 350°C for 3-5 sec

Mates with (Subject to pin length)
BC065 BC070 BC075

No. of Contacts	Dimensions	
	A	B
2	1.00	2.00
3	2.00	3.00
4	3.00	4.00
5	4.00	5.00
6	5.00	6.00
7	6.00	7.00
8	7.00	8.00
9	8.00	9.00
10	9.00	10.00
11	10.00	11.00
12	11.00	12.00
13	12.00	13.00
14	13.00	14.00
15	14.00	15.00
16	15.00	16.00
17	16.00	17.00
18	17.00	18.00
19	18.00	19.00
20	19.00	20.00
21	20.00	21.00
22	21.00	22.00
23	22.00	23.00
24	23.00	24.00
25	24.00	25.00
26	25.00	26.00
27	26.00	27.00
28	27.00	28.00
29	28.00	29.00
30	29.00	30.00
31	30.00	31.00
32	31.00	32.00
33	32.00	33.00
34	33.00	34.00
35	34.00	35.00
36	35.00	36.00
37	36.00	37.00
38	37.00	38.00
39	38.00	39.00
40	39.00	40.00

Ordering Grid

BC030 - XX - X - XXXX - XXXX - XXXX - L - X

No. of Contacts: 02 to 40

Contact Plating:
A = Gold Flash All Over (Standard)
C = Tin All Over

Dimension C (1/100mm) (Post Height)
0200 = 2.00mm (Standard)
or specify Dimension C
eg. 0250 = 2.50mm
Tol +/- 0.2mm
(Maximum 0600=6.00mm)
(Minimum 0100=1.00mm)

Dimension D (1/100mm) (Top of Insulator to Pin Bend)
0140 = 1.40mm (Standard)
or specify Dimension D
eg. 0250 = 2.50mm
Tol +/- 0.2mm
(Maximum 0500=5.00mm)
(Minimum 0130=1.30mm)

Dimension E (1/100mm) (Tail Length)
0250 = 2.50mm (Standard)
or specify Dimension E
eg. 0450 = 4.50mm
Tol +/- 0.2mm
(Maximum 0500=5.00mm)
(Minimum 0100=1.00mm)

Packing Options
G = Plastic Box (Standard)
D = Tube
E = Tube with Cap

Insulator Material
L = LCP (Standard)

Part Number		Product Description	
BC030		1.0mm Pitch Pin Header, Single Row, Through-Hole, Horizontal	
Drawing Date		20th May 2008	
By	CC	Tolerances (Except as Noted)	Units:
Detail	BC030 C PCN	Length X. ± 0.30 X.X ± 0.25 X.XX ± 0.15 X.XXX ± 0.10	Metric (mm)
Revision	C1	Angle X.° ± 5° X.X° ± 3° X.XX° ± 2° X.XXX° ± 1°	3rd Angle Projection
Date	26/09/17		



This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE



Not to Scale	Drawn By ASE	Sheet No. 1/1
--------------	--------------	---------------